

Online Ups 1KVA 2KVA 3KVA



- Pure sine wave output
- LED display
- Built-in battery type
- External battery
- Internal slot SNMP/AS400 card optional
- SNMP card optional
- With RS232&RJ45 with USB(optional)



Offline Series UPS Specification

MODEL	HD-1K1	HD-1K1S	HD-2K1	HD-2K1S	HD-3K1	HD-3K1S
Capacity(VA/W)	1000VA/700W		2000VA/1400W		3000VA/2100W	
INPUT						
Phase	1PH 2W+G					
Voltage Range	115~300VAC					
Frequency	46~64Hz; 50/60Hz Autoadaptation					
Power Factor	>0.99					
OUTPUT						
Voltage Range	220x(1±1%)VAC					
Frequency Range	Main mode:(46~54)Hz/(56~64)Hz			Battery mode:50(±0.1%)Hz/60(±1%)Hz		
Crest Ratio	3:1					
Power Factor	0.7					
Output Waveform	Pure Sine Wave					
Outlet	IECx4		IECx4		IECx3+Terminal	
TRANSFER TIME						
Transfer Time	Zero					
Inverter To Bypass	Zero					
INDICATOR						
LED	Load/ Battery capacity/Main mode/Bypass mode/Fault					
LCD	Load/Battery/Input/Output/Operation Mode					
ENVIRONMENT						
Operating Environment	0~40℃					
Humidity	20-90%(non-condensing)					
Noise	<60db@1Meter					
Temperature	-25℃~55℃(no battery)					
OTHER						
Protection	Load<105%,Keep working;		105%<Load≤125% >1min;		125%<Load≤150% >30sec	
Efficiency	Up to 90%					
Battery Inbuilt	3pcs x 12V/ 7.2AH			8pcs x 12V/ 7.2AH		
Battery DC Voltage	DC36V			DC96V		
PHYSICAL						
Dimension DxWxH(mm)	400x145x220		460x192x348		460x192x348	
Net Weight(kgs)	14	7	31	13.5	31.5	14

* Product specifications are subject to change without further notice.